

### Local Authority Building Standards Scotland [LABSS]



formerly the Scottish Association of Building Standards Managers [SABSM]

# House Type Approval Certificate

 Certificate No:
 STAS/15/015/DM50/09/AMD01

 Date:
 22 March 2017

A Certificate Holder:
Springfield Properties, Springfield House, 3 Central Park Avenue, Larbert, FK5 4RX

E-mail: gregor.robertson@springfield.co.uk Tel: 01324 555536

В	House Type Titles:				
	Description:	2015 Uplift	Doune - 3B 1020te semi-detached two storey house (included)	ding mid	
		•	terraced option)		

The domestic type approval has been assessed on the following drawings and specifications:

See attached annexe to this certificate

Wind: (as defined in BS 6399-2)	Standard effective wind speed, Ve =	44.1 m/s
	For maximum effective height =	10.0m
	Has funnelling been considered?	NO
Winds (as defined in CD2: Chapter	Design wind around Vo =	25.5 m/s
Wind: (as defined in CP3: Chapter	Design wind speed, Vs =	23.3 111/5
V)	(relevant to the building frame, at a height of 3m or less)	
Snow: (as defined in BS 6399-3)	Site snow load. So =	0.75 Kn/m2
onow. (as defined in DO 0000-0)	Influenced by adjacent buildings?	NO
	initidenced by adjacent buildings:	110
Resistance to moisture/durability	Max exposure (to wind driven rain) grading, as defined in BRE Report –	Zone 4
of exposed elements:	Thermal Insulation: Avoiding Risks, Second Edition, 1994, to be exposure	ZOIIC 4
oi exposed elements.	zone:	
	Exposure to sea spray (i.e. coastal region) or de-icing salts?	
	Other air contaminants or biological factors – please specify any	
	enhanced resistance if applicable (refer to BS7543 for guidance)	NO
	entranced resistance ir applicable (refer to B57545 for guidance)	NO
Design Life: (per BS 7543 -	Catagony of building decign life -	60 voore
	Category of building design life =	60 years
Durability of buildings and building		•
elements, products and components)	Design life of primary building envelope	60 years

#### E Conditions of certification:

- The design shown and the specifications and materials referred to have been assessed and approved in accordance with the Building (Scotland) Regulations 2004 and in accordance with the supporting guidance in the Domestic Technical Handbooks which came into force with effect from 1 October 2015.
- 2. The certificate shall be valid until invalidated by formal notice by the Local Authority Building Standards Scotland
- 3. The design shown and the materials specified shall not be changed without reference to the Local Authority Building Standards Scotland responsible for certifying the system.
- 4. Where reference is made on a plan or specification document to any Code of Practice, British or European Standard or manufacturer's instruction it shall be construed as a reference to such publication in the form in which it is in force at the date of this certificate.
- 5. This certificate should not be regarded as a formal approval under the building warrant process prescribed by the Building (Scotland) Act 2003 enacted from 1 May 2005
- 6. The Bill Henderson Consulting Engineer Ltd amended statement dated 7 February 2017 referenced here under Section G, confirm that a structural appraisal has been carried out. Further site-specific information MUST BE made available when a site-specific building warrant is sought. Such additional information should take cognisance of Procedural Guidance on Certification including information to be submitted with a Building Warrant Application dated April 2010 Version 2. Confirmation of a holistic approach to structural adequacy of the entire completed building shall be provided by a registered engineer to the local authority within whose area the site specific dwelling is to be built.





**Local Authority Building Standards Scotland [LABSS]** formerly the Scottish Association of Building Standards Managers [SABSM]

Annexe of drawings, certificates and specification documents used in the assessment:

F	Drawing Number:	Description:		
	1020te(AS)103	Plot Works Layout, Gas & Air Source Heat Pump Hybrid Heating		
	1020te(AS)301 K	Ground Floor General Arrangement		
	1020te(AS)305 H	First Floor Services Layout		
	1020te(AS)324 A	Ground Floor Services Layout, Gas & Air Source Heat Pump Hybrid Heating		
	1020te(AS)421 A	Elevations showing PV Location, Gas & Air Source Heat Pump Hybrid Heating		
	1020te(AS)701 H	Accessible Cloakroom Layout		

G	Certification:		
	BRE Global Ltd Certificate of Design	For all house types	
	(Section6 – Energy)		
	BRE-S6-1-02534		
	Amended Statement of structural	From Bill Henderson Consulting Engineer Ltd dated 7 February 2017	
	adequacy	,	

Н	Specification:	
	Springfield – 2015 Building Standards	For all house types
	Technical Specification	
	Mainstream Housing - Timber Frame,	
	Hybrid Air Source Heat Pump & Gas	
	Central Heating	
	Revision G 21/03/2017	
	Stroma SAP ratings	For all house types
	SAP 2012	
	Sustainability	For all house types
	Bronze Active Level - 06/02/17	
	U-value calculation	Floor – DOUNE 0.17
	U-value calculation	External Wall
	U-value calculation	Main Roof (
	Robust Wall specification	Bill Henderson Consulting Engineer Ltd – letter and fixing specification dated 7 March 2017

1	Authority:		
	This system type approval certificate consisting of 2 pages is authorised by:	Signature:	Daellee,
	, (7)		Lead Authority Building standards Manager

## Appendix A

Regulation 9	Decision
Provisions on which an alternative approach is given	
Technical Standard 3.12 Sanitary facilities (Domestic)	
Guidance Clause 3.12.3 of the technical handbook for dwellings identifies that walls adjacent to any sanitary facility are of robust construction that will permit secure fixing of grab rails or other aids in the zones noted in figure 3.32	Robust walls to structural engineer's specification (Bill Henderson Consulting Engineer Ltd letter and fixing specification dated 7 March 2017)