

This certificate is valid for Building Regulations & associated technical guidance in force on the date of registration and for the regulations in the countries indicated

Gerband Split Release Tapes

Description of Product

This is an assessment of Gerband 88/12 split release tape, Gerband 48/12 split release tape, and Gerband 50/50 split release tape.

Gerband 88/12 & 48/12 are pliable stretchable PE-film sealing tapes with moisture-resistant polyacrylate adhesive of extremely high tack and permanent adhesion as well as ageing resistance.

The Gerband 50-50 split release tape (100mm wide) is a pliable stretchable PE-film sealing tape with moisture-resistant polyacrylate adhesive of extremely high tack and permanent adhesion as well as ageing resistance.



Key Factors Assessed

- Mechanical Resistance & Stability
- Health, Hygiene and Environmental
- Safety in Use
- Energy Economy and heat retention
- Durability serviceability and identification

Validity

This certificate was first issued on 7th October 2016 and is valid until 7th October 2017

Issue Dated 7th October 2016

Scope of Registration

The split release permits the installer to quickly apply the tapes to the window frame reveals and floor to wall junctions in separate and manageable steps, the PET reinforcement also helps preventing over expansion of the adhesive tape.

Gerband 88/12 & 48/12 tapes are to be used indoors for the air-tight bonding and sealing of vapour barriers to door and window reveals.

The Gerband 50/50 tape is used, for example, to seal vapour barriers to floor and wall junctions.

Conditions of Certificate

Surfaces must be stable, dry, free of grease and dust, and must not contain adhesive-repellent coatings, some MDF and masonry surface may need a primer coating (such as Primer 6300) for best results.

The installer should firstly apply a sample of the tape and test adhesion.

For Scotland Purposes:

The specifications and materials referred to have been assessed in accordance with the Building (Scotland) Regulations 2004 and in accordance with the supporting guidance in the Domestic Technical Handbooks which came into force with effect from 1 June 2016.

Where reference is made on a plan or specification document to any Code of Practice, British or European Standard or manufacturer's instruction it shall be construed as a reference to such publication in the form in which it is in force at the date of this Registered Detail.

The materials specified shall be for purposes of this Registered Detail and should not be changed without first gaining approval so to do from Local Authority Building Standards Scotland [LABSS]. Failure to do so will invalidate the Registered Detail.

The Registered Detail shall be valid for a period of 12 months from the date of issue or until otherwise invalidated by formal notice by LABSS. The Registered Detail may be re-validated after 12 months following a request and payment of an annual renewal fee from the Registered Detail Holder.

This Registered Detail should not be regarded as a formal approval under the building warrant process prescribed by the Building (Scotland) Act 2003 enacted from 1 May 2005.

This Registered Detail shall contribute to compliance with relevant Mandatory Standards specified under the Building (Scotland) Regulations 2004 as amended when read with the scope, conditions and regulations sections to this Registered Detail.

LABC and LABSS consider that, Gerbrand Split Release Tapes will meet the functional requirements of the Building Regulations (listed below) if the criteria detailed in this certificate are met;



The Building Regulations 2010 (as amended) England & Wales

Regulation 7	Materials and Workmanship
Note:	The products are acceptable.
AD C	Resistance to Moisture
Note:	The products are acceptable.
AD L1A	Conservation of Fuel and Power
Note:	The products contribute to the overall performance of the structure.



The Building Regulations 2010 (as amended) England

AD L1A	Conservation of Fuel and Power
Note:	The products contribute to the overall performance of the structure.



The Building Regulations 2010 (as amended) Wales

AD L1A	Conservation of Fuel and Power
Note:	The products contribute to the overall performance of the structure.



The Building (Scotland) Regulations 2004 (as amended)

Technical Handbooks Domestic and Non-Domestic

Regulation 8(1)	Durability, workmanship and fitness of materials
0.8.5:	Ways of establishing the fitness of materials
Regulation 9	Building Standards applicable to construction
Note:	Construction shall be carried out so that the work complies with the applicable requirements of schedule 5.
Mandatory	
Standard 3.15	Condensation
Note:	The product can contribute to satisfying this standard, with reference to clauses 3.15.1, 3.15.4 and 3.15.5 of the domestic and non-domestic technical handbooks. A site specific condensation analysis should be provided.

Mandatory	
Standard 6.1(b)	Carbon Dioxide Emissions
Note:	The thermal insulation performance of this product should be considered in the context of the contribution made to the overall performance of the building.
Mandatory	
Standard 6.2	Building Insulation Envelope
Note:	The thermal insulation performance of this product should be considered in the context of the contribution made to the overall performance of the building.

Non-Regulatory Information



LABC Warranty
Pending assessment

Supporting Documentation

ISO 9001:2008 certificate

Contact Information

Passive House Systems (UK)

Brickfield House

High Road

Thornwood

Epping

Essex

CM16 6TH

Tel: 0845 4591500

Email: info@passivehousesystems.co.uk

Web: www.passivehousesystems.co.uk