

## Local Authority Building Standards Scotland [LABSS]



formerly the Scottish Association of Building Standards Managers [SABSM]

# House Type Approval Certificate

Certificate No: STAS/16/015/DM57/06

Date: 03 March 2017

A Certificate Holder:

Springfield Properties, Springfield House, 3 Central Park Avenue, Larbert, FK5 4RX

E-mail: gregor.robertson@springfield.co.uk Tel: 01324 555536

| House Type Titles:
| Description: | Nairn – 3B 1237DT detached two storey house with integrated garage

The domestic type approval has been assessed on the following drawings and specifications:

See attached annexe to this certificate

Att d- ( d-6d-6- DO 0000 0)	15 11 20 2000 21 101 11 11 11	
Wind: (as defined in BS 6399-2)	Standard effective wind speed, Ve =	44.1 m/s
	For maximum effective height =	10.0m
	Has funnelling been considered?	NO
Alter de la constant de CD2 Observa	Design wheel second 1/s	05.5/-
<b>Wind:</b> (as defined in CP3: Chapter	Design wind speed, Vs =	25.5 m/s
/)	(relevant to the building frame, at a height of 3m or less)	
S ( defined in DC (200-2)	Cite ensuring Co -	0.75 V m/m 2
Snow: (as defined in BS 6399-3)	Site snow load, So =	0.75 Kn/m2
	Influenced by adjacent buildings?	NO
Resistance to moisture/durability	Max exposure (to wind driven rain) grading, as defined in BRE Report –	Zone 4
of exposed elements:	Thermal Insulation: Avoiding Risks, Second Edition, 1994, to be exposure	
	zone:	
	Exposure to sea spray (i.e. coastal region) or de-icing salts?	
	Other air contaminants or biological factors – please specify any	
	enhanced resistance if applicable (refer to BS7543 for guidance)	NO
Design Life: (per BS 7543 –	Category of building design life =	60 years
Durability of buildings and building		30 , 000
Durability of buildings and building		

### E Conditions of certification:

- The design shown and the specifications and materials referred to have been assessed and approved in accordance with the Building (Scotland) Regulations 2004 and in accordance with the supporting guidance in the Domestic Technical Handbooks which came into force with effect from 1 October 2013.
- 2. The certificate shall be valid until invalidated by formal notice by the Local Authority Building Standards Scotland
- 3. The design shown and the materials specified shall not be changed without reference to the Local Authority Building Standards Scotland responsible for certifying the system.
- 4. Where reference is made on a plan or specification document to any Code of Practice, British or European Standard or manufacturer's instruction it shall be construed as a reference to such publication in the form in which it is in force at the date of this certificate.
- This certificate should not be regarded as a formal approval under the building warrant process prescribed by the Building (S cotland) Act 2003 enacted from 1 May 2005
- 6. The Bill Henderson Consulting Engineer Ltd statement dated 2 September 2016 referenced here under Section G, confirm that a structural appraisal has been carried out. Further site-specific information MUST BE made available when a site-specific building warrant is sought. Such additional information should take cognisance of Procedural Guidance on Certification including information to be submitted with a Building Warrant Application dated April 2010 Version 2. Confirmation of a holistic approach to structural adequacy of the <a href="mailto:entire completed">entire completed</a> building shall be provided by a registered engineer to the local authority within whose area the site specific dwelling is to be built.





**Local Authority Building Standards Scotland [LABSS]** formerly the Scottish Association of Building Standards Managers [SABSM]

Annexe of drawings, certificates and specification documents used in the assessment:

	nexe of drawings, certificates and specification documents used in the assessment:			
F	Drawing Number:	Description:		
	1237dt(AS)001 A	Schedules State Leave to the Control of the Control		
	1237dt(AS)101 A	Plot Works Layout		
	1237dt(AS)205 A	Drainage Isometric		
	1237dt(AS)301 B	Ground Floor General Arrangement		
	1237dt(AS)302 A	First Floor General Arrangement		
	1237dt(AS)304 A	Ground Floor Services Layout		
	1237dt(AS)305 B	First Floor Services Layout		
	1237dt(AS)401 C	Elevations		
	1237dt(AS)501 A	Section A-A		
	1237dt(AS)502 A	Section B-B		
	1237dt(AS)503 B	Stair Sections Stair Sections		
	1237dt(AS)504 A	Stair Plans		
	1237dt(AS)601 B	Floor Joist Layout		
	1237dt(AS)602 C	Roof Plan		
	1237dt(AS)701 B	Accessible Cloakroom Layout		
	J10206_Nairn	Finnjoist (FJI) Kerto LVL		
	Q17388AM	Roof Truss Layout		
	608 S1 W1	Structural Notes Timber Frame Construction		
	608 S2 W3	Timber Frame Typical Details Ground Bearing Floor Slab		
	608 S5 W1	Timber Frame Typical Details Suspended Slab		
	DET(TK)03-01 B	Ground Floor Detail with Suspended Slab, Polished Finish		
	DET(TK)03-02 A	Ground Floor Detail with Ground Bearing Slab, Polished Finish		
	DET(TK)03-07 B	Dwarf Wall Detail with Suspended Slab, Polished Finish		
	DET(TK)04-02 B	External Wall, Internal & External Corner Detail		
	DET(TK)04-06 -	External Wall to Party Wall Detail		
	DET(TK)05-01 C	Typical Cavity Barrier Positions		
	DET(TK)08-01 B	Mid Floor Detail at External Wall, Parallel Joists		
	DET(TK)08-02 B	Mid Floor Detail at External Wall, Perpendicular Joists		
	DET(TK)08-03 B	Mid Floor Detail at External Wall, Parallel Joists		
	DET(TK)11-07 B	40 degrees Eaves Detail at First Floor Wall Head		
	DET(TK)11-08 B	40 degrees Eaves Detail at First Floor Window Head		
	DET(TK)11-12 B	Verge Detail		
	DET(TK)14-01 B	Window Cill Detail – Ground Floor, Render		
	DET(TK)14-02 B	Window Cill Detail - First Floor, Render		
	DET(TK)14-05 A	Window Jamb Detail - Render		
	DET(TK)14-07 B	Window Head Detail – Ground Floor, Render		
	DET(TK)14-08 B	Window Head Detail - First Floor, Render		
	DET(TK)15-01 A	External Door Detail Level Access Threshold Polished Slab Finish		
	DET(TK)15-02 A	External Door Detail Stepped Access Threshold Polished Slab Finish		
	DET(TK)29-01	Timber Kit Hold Down strap Detail		
	DET(TK)29-02	Typical Roof Fixing Details Page 1		
	DET(TK)29-03	Typical Roof Fixing Details Page 2		
	DET(TK)29-04	Typical Roof Fixing Details Page 3		
	DET(TK)29-05	Typical Roof Fixing Details Page 4		
	CAS 8499_26	Vent Axia Nairn 1237DT		
	608 S(NAIR)25 Rev B	Structural overlay		
		· · · · · · · · · · · · · · · · · · ·		

G	Certification:	
	BRE Global Ltd Certificate of Design	For all house types
	(Section6 – Energy)	
STAS/13/053/RD06/01 Registered detail certificate for ventila		Registered detail certificate for ventilation system
	Statement of structural adequacy	From Bill Henderson Consulting Engineer Ltd dated 2 September 2016

Н	Specification: Springfield – Technical Specification – Mainstream Housing, Bronze Standard Compliant Gas Central Heating Revision M	For all house types
	Stroma SAP ratings	For all house types



# Local Authority Building Standards Scotland [LABSS]



formerly the Scottish Association of Building Standards Managers [SABSM]

	BRE report	Intermediate Floor sound test
Sound test c/03/5L/0835/1 Intermediate Floor sound test report		Intermediate Floor sound test report
	Vent Axia Lo-carbon dMEV unit	Manufacturers information for ventilation system
	Bill Henderson Consulting Engineer	Introduction
	Ltd Calculation Sheet 608(i)W1	
	Bill Henderson Consulting Engineer	Notes for Timber Kit manufacture
	Ltd Calculation Sheet 608(ii)W2	

-1	Authority:		
	This system type approval certificate consisting of 3 pages is authorised by:	Signature:	andlee.
	Lead Authority Building standards Manage on behalf of the Local Authority Building Standards Scotland (LABSS		

Appendix A

Regulation 9	Decision	STAS Condition
Provisions on which dispensation is given		