

Local Authority Building Standards Scotland [LABSS]



formerly the Scottish Association of Building Standards Managers [SABSM]

House Type Approval Certificate

 Certificate No:
 STAS/18/015/DM90/04

 Date:
 5 March 2019

Certificate Holder:

Springfield Properties Springfield House 3 Central Park Avenue Larbert FK5 4RX
E-mail: Jamie.Russell@springfield.co.uk

Tel: 01324 555 536

В	House Type Titles:		
	Description:	2017 Standards	ROSEISLE DETACHED HOUSE TYPE

The domestic type approval has been assessed on the following drawings and specifications:

See attached annexe to this certificate

(relevant to the building frame, at a height of 3m or less) Show: (as defined in BS 6399-3) Site snow load, So =	For r	ard effective wind speed, Ve = aximum effective height = nnelling been considered?	44.1 m/s 10 m NO
Influenced by adjacent buildings? Resistance to moisture/durability of exposed elements: Max exposure (to wind driven rain) grading, as defined in BRE Report – Thermal Insulation: Avoiding Risks, Second Edition, 1994, to be exposure zone: Exposure to sea spray (i.e. coastal region) or de-icing salts? Other air contaminants or biological factors – please specify any	·	•	25.5m/s
of exposed elements: Thermal Insulation: Avoiding Risks, Second Edition, 1994, to be exposure zone: Exposure to sea spray (i.e. coastal region) or de-icing salts? Other air contaminants or biological factors – please specify any		e eest eest eest eest eest eest eest ee	0.75 KN/m2 No
enhanced resistance if applicable (refer to BS7543 for guidance) N	ments: There zone Expo	al Insulation: Avoiding Risks, Second Edition, 1994, to be exposure ure to sea spray (i.e. coastal region) or de-icing salts? air contaminants or biological factors – please specify any	Exposure Zone/- 4
	enha	ced resistance if applicable (refer to BS7543 for guidance)	No
Design Life: (per BS 7543 – Category of building design life = 60 ye	er BS 7543 – Cate	ory of building design life =	60 years

Conditions of certification:

- The design shown and the specifications and materials referred to have been assessed and approved in accordance with the Building (Scotland) Regulations 2004 and in accordance with the supporting guidance in the Domestic Technical Handbooks which came into force with effect from 1 July 2017.
- 2. The certificate shall be valid until invalidated by formal notice by the Local Authority Building Standards Scotland
- 3. The design shown and the materials specified shall not be changed without reference to the Local Authority Building Standards Scotland responsible for certifying the system.
- 4. Where reference is made on a plan or specification document to any Code of Practice, British or European Standard or manufacturer's instruction it shall be construed as a reference to such publication in the form in which it is in force at the date of this certificate.
- 5. This certificate should not be regarded as a formal approval under the building warrant process prescribed by the Building (Scotland) Act 2003 enacted from 1 May 2005
- 6. Bill Henderson Consulting Engineer Ltd Statement of Structural Adequacy STAS/18/015/DM90 1 to 4 referenced here under Section G, confirm that a structural appraisal has been carried out. Further site-specific information MUST BE made available when a site-specific building warrant is sought. Such additional information should take cognisance of Procedural Guidance on Certification including information to be submitted with a Building Warrant Application dated April 2010 Version 2. Confirmation of a holistic approach to structural adequacy of the entire completed building shall be provided by a registered engineer to the local authority within whose area the site-specific dwelling is to be built.





Local Authority Building Standards Scotland [LABSS] formerly the Scottish Association of Building Standards Managers [SABSM]

Annexe of drawings, certificates and specification documents used in the assessment:

Drawing Number:	Description:
Roseisle 735bwD(as)-001a	Data Sheet
Roseisle 735bwD(as)-103	Plot Layout
Roseisle 735bwD(as)-205	Drainage Isometric
Roseisle 735bwD(as)-301	Ground Floor Plan
Roseisle 735bwD(as)-323g	Services Layout
Roseisle 735bwD(as)-421c	Elevations
Roseisle 735bwD(as)-501a	Section A-A
Roseisle 735bwD(as)-502a	Section B-B
Roseisle 735bwD(as)-601	Roof Plan
Roseisle 735bwD(as)-701a	Bathroom Layout
DET(TK)03-02d	Ground Floor Detail with Ground Bearing Slab Polished Floor
DET(TK)03-16a	Garage Floor Detail
DET(TK)04-02c	Internal & External CornerCullen
DET(TK)04-03b	Internal & External Corner - Timber Cladding
DET(TK)04-04b	Timber Cladding Detail at Vertical Junction to Masonry
DET(TK)04-05b	Timber Cladding Detail at Voltage surface to Masonry Timber Cladding Detail at Horizontal Junction to Masonry
DET(TK)04-03b	External Wall to Party Wall Detail
DET(TK)05-005 DET(TK)05-01e	Cavity Barrier Positions
DET(TK)06-21d	Party Wall Detail at Ceiling - No Step
DET(TK)06-21d DET(TK)06-31e	Party Wall Detail at Ceiling - No Step Party Wall Detail at Roof - No Step
DET(TK)06-31e DET(TK)06-36a	Party Wall Detail at Roor - No Step Party Wall GF Detail with Ground Bearing Slab Polished Floor
DET(TK)06-41d	3D Party Wall Fireproofing Detail
DET(TK)07-03a	Internal Partition Make Up
DET(TK)11-07d DET(TK)11-08d	40deg Eaves Detail at Wall Head
	40deg Eaves Detail at Window Head
DET(TK)11-12c	Verge Detail
DET(TK)11-13b	Valley Detail
DET(TK)11-19	3D Eaves Detail
DET(TK)11-25	Concrete Ridge with Concrete Roof Tile Detail
DET(TK)14-01c	Window Cill Detail - Render
DET(TK)14-03c	Window Cill Detail - Cladding
DET(TK)14-05b	Window Jamb Detail - Render
DET(TK)14-06f	Window Jamb Detail - Cladding
DET(TK)14-07c	Window Head Detail - Ground Floor, Render
DET(TK)14-08c	Window Head Detail - Top Floor, Render
DET(TK)14-09f	Window Head Detail - Ground Floor, Cladding
DET(TK)14-10d	Window Head Detail - Top Floor, Cladding
DET(TK)15-05b	Garage Door Threshold Detail
DET(TK)15-06a	External Door Stepped Threshold Detail - Ground Bearing Slab
DET(TK)15-07a	External Door Level Threshold Detail - Ground Bearing Slab
DET(TK)15-11	Garage Door Detail
DET(TK)19-01b	Boiler Flue Detail
DET(TK)21-01b	Electrical Legend & Installation Guide
DET(TK)29-01	Timber Kit Hold Down Strap Detail
DET(TK)29-02	Typical Roof Fixing Details Page 1
DET(TK)29-03	Typical Roof Fixing Details Page 2
DET(TK)29-04	Typical Roof Fixing Details Page 3
DET(TK)29-05	Typical Roof Fixing Details Page 4
Structural Engineers Drawings	
608 S ROSID 25	Overmarked Floor Plan
Certificate of Design (Building Structures)	Certificate Number 284797
SPRSTAS S1	Structural Notes
SPRSTAS S2	Structural Details
STAS pages Oct2018	Structural Information
Vent-Axia Design Drawings	
CAS 10408 45 - Roseisle 735dwD (As)	Vent-Axia Layout
Registered Detail	STAS/13/053/RD06/01
Roof Truss Drawings	·
Q18802FT 01 Roseisle Detached Truss Layout	
Q18802FT 03 Roseisle Detached	
Truss Profiles AS	





Local Authority Building Standards Scotland [LABSS] formerly the Scottish Association of Building Standards Managers [SABSM]

G	Certification	
	Statement of Structural Adequacy	Bill Henderson Consulting Engineer Ltd SSA STAS 18015 DM90 1 to 4
	Certificate of Design (Section 6 – Energy)	BRE-S6-1-03023
	TER/DER SAP Version 1.0.4.10 Compliance	Roseisle House Type Compliance Report
	Report	
	External Wall u-value Calculation	2015 Regs External Hybrid Only
	Sustainability Certificate	Roseisle Detached Sustainability Label
	Garage/House wall U-value	2015 Regs Garage-House Wall
	Ceiling U-value	2015 Regs Level Ceiling Rev A
	Floor U-value	Roseisle 0.17
	Sound	Charlie Fleming Associates Letter dated 7 December 2014 Ref 2464#01#L

Н	Specification	
	Springfield	2017 Technical Specification – Mainstream Housing - Timber Frame- Bungalows – Hybrid Air Source
		Heat Pump & Gas Central Heating - Dated 22 August 2018

Authority:		
This system type approval certificate consisting of 3 pages is authorised by:	Perth and Kinross Council	
	on behalf of the Local Authority Building Standards Scotland (LABSS)	