



House Type Approval Certificate

Certificate No: Date: STAS/17/O56/DM77/06 12 December 2018

А	Certificate Holder:				
Λ					
	Barratt East Scotland Telford Ho	Barratt East Scotland Telford House, 3 New Mid Cutlins, EDINBURGH EH11 4DH			
	E-mail: matthew.watson@barrat				
	¥				
В	House Type Titles:				
	Description: 2017 Standards	DALMALLY H411R-S7 DETACHED	4		
С	The domestic type approval has been	The domestic type approval has been assessed on the following drawings and specifications:			
		nnexe to this certificate			
D	Climatic conditions: The design may	Climatic conditions: The design may be built in areas where the climatic conditions are equal to or less than those detailed below:			
	Wind: (as defined in BS 6399-2)	Standard effective wind speed, Ve =	41.4 m/s		
		For maximum effective height =	8.5 m		
		Has funnelling been considered?	NO		
	Winds (as defined in OD2) Obserter		NVA		
	Wind: (as defined in CP3: Chapter V)	Design wind speed, Vs = (relevant to the building frame, at a height of 3m or less)	N/A		
	•)				
	Snow: (as defined in BS 6399-3)	Site snow load, So =	0.64 Kn/m2		
	- (,	Influenced by adjacent buildings?	No		
	Resistance to moisture/durability	Max exposure (to wind driven rain) grading, as defined in BRE Report -	Exposure Zones 1, 2, 3 and 4		
	of exposed elements:	Thermal Insulation: Avoiding Risks, Second Edition, 1994, to be			
		exposure zone: Exposure to sea spray (i.e. coastal region) or de-icing salts?			
		Other air contaminants or biological factors – please specify any			
		enhanced resistance if applicable (refer to BS7543 for guidance)	Yes/No		
	Design Life: (per BS 7543 –	Category of building design life =	60 years		
	Durability of buildings and building	Design life of primery building envelope	60 маста		
	elements, products and components)	Design life of primary building envelope	60 years		
Е	Conditions of certification:				
		ecifications and materials referred to have been assessed and approved in a			
	(Scotland) Regulations 2004 a	nd in accordance with the supporting guidance in the Domestic Technical H	andbooks which came into force		
	with effect from 1 July 2014.	 with effect from 1 July 2017. The certificate shall be valid until invalidated by formal notice by the Local Authority Building Standards Scotland 			
		terials specified shall not be changed without reference to the Local Authority			
	responsible for certifying the s		y Danany Olandarus Ololianu		
	instruction it shall be construed	instruction if shall be construed as a reference to such publication in the form in which it is in force at the date of this certificate.			
	5. This certificate should not be regarded as a formal approval under the building warrant process prescribed by the Building (Scotland) Act 2003 enacted from 1 May 2005				
	6. Bayne Stevenson Associates Ltd structural calculations dated 12 April 2017 Revision G (411 Detached) referenced here under Section G,				
	confirm that a structural appraisal has been carried out. Further site-specific information MUST BE made available when a site-specific				

building warrant is sought. Such additional information should take cognisance of Procedural Guidance on Certification including information to be submitted with a Building Warrant Application dated April 2010 Version 2. Confirmation of a holistic approach to structural adequacy of the <u>entire completed building</u> shall be provided by a registered engineer to the local authority within whose area the site-specific dwelling is to be built.

F Authority:

 Addivity	
This system type approval certificate consisting of 3 pages is authorised by:	ANGUS COUNCIL as Lead Authority
	on behalf of the Local Authority Building Standards Scotland (LABSS)





Annexe of drawings, certificates and specification documents used in the assessment:

G	Certification	
	Structural	• <u>SC_411_2016_V9.PDF</u>
	Calculations	
	Section 6 2017	 DER WORKSHEET SECTION 6 2017 - H411R-S7 DALMALLY (DETACHED EAST WEST).PDF
		SCOTLAND SECTION 6 2017 - REG COMPLIANCE REPORT - H411R-S7 DALMALLY (DET.PDF
		TER WORKSHEET SECTION 6 2017 - H411R-S7 DALMALLY (DETACHED EAST WEST).PDF

Н	Specification			
	BARRATT SCOTLAND	2015 Spec Rev B 04/09/17 Detached & Attached Two & Three Storey Timber Frame		
	Specification Caledonia & Alba Range 2015 Technical Standards	Houses		
l.	Drawing Number:	Description:		
	Floor and Block Layouts			
	• <u>H411R-S7 DS02.PDF</u>			
	<u>17-H411-PLOT_BLOCK LAYOUTS_AFUPLOT LAYOUTPDF</u>			
	Stormking Details			
	• BBA 06 - 4356l1.PDF			
	DWH T ALB17 H T365 RIS7 NEWMAR	CHAR GRP - STORMKING - TERRACE MID AFU PDF		
	RAWLPLUG FF1 FIXINGS.PDF			
	STORM KING ENTRANCE CANOPY FIX	ING DETAILS.PDF		
	• STORMKING FIXING DETAILS.PDF			
	•			
	External Wall Details			
	DB-SSD02-T601 PARTY EXTERNAL WALL EJ DETAIL.PDF			
	DB-SSD02-T602 EXTERNAL WALL COR	NER JUNCTION.PDF		
	DB-SSD02-T603 EXTERNAL INTERNAL CORNER JUNCTION.PDF			
	DB-SSD02-T604 HOUSE GARAGE/EXTERNAL WALL JUNCTION.PDF			
	DB-SSD02-T605 STAGGERED PART			
		ALL JUNCTION NO SERVICE ZONE.PDF		
	DB-SSD02-T607 STEEL RACKING FRAM			
	DB-SSD02-T608 STEEL GONL-POST IN DB-SSD02-T608 STEEL GONL-POST IN DB-SSD02-T608 STEEL GONL-POST IN			
	DB-SSD02-T609B RENDER TIMBER INFILL PANEL.PDF			
	DB-SSD02-T610A RENDER TIMBER INFILL PANEL SHEET 2.PDF			
	Floor Details			
	DB-SSD04-F601 SUSPENDED SLAB EX	TERNAL WALL.PDF		
	DB-SSD04-T602 SUSPENDED SLAB PA	RTY WALL.PDF		
	DE-SSL04-1603A INTERNAL WALL GARAGE FLOOR.PDF			
	DB SSD04-T604 EXTERNAL WALL GARAGE FLOOR.PDF			
	DL-SSD04-T605A INTERMEDIATE FLOOR EXTERNAL WALL.PDF			
	B-SSD04-T606A INTERMEDIATE FLOO			
	DB-SSD04-T607 INTERMEDIATE FLOOP	R GARAGE WALL.PDF		
	DB-SSD04-T608 INTERMEDIATE FLOOR GARAGE HOUSE WALL.PDF			
	DB-SSD04-T609 SUSPENDED SLAB EXTERNAL WALL TEMP SHUTTERING.PDF			
	DB-SSD04-T610 SUSPENDED SLAB 675			
	DB-SSD04-T611 SUSPENDED SLAB 900MM STEPPED PARTY WALL.PDF			





perphi

Roof Details

- BH-SSD05-T601 WET VERGE DETAIL.PDF
- BH-SSD05-T602 DRY VERGE DETAIL.PDF •
- BH-SSD05-T603 EAVES DETAIL 35 DEGREE.PDF
- BH-SSD05-T604 EAVES DETAIL 35 DEGREE WITH WINDOW.PDF
- DB-SSD05-T601 PARTY WALL COLD ROOF.PDF
- DB-SSD05-T602 PARTY WALL WARM ROOF.PDF
- DB-SSD05-T603 STEPPED PARTY WALL ROOF LEVEL.PDF

Door Details

- DB-SSD06-T601 IG FRONT DOOR THRESHOLD.PDF
- DB-SSD06-T602 DOOR JAMB DETAIL.PDF
- DB-SSD06-T603 DOOR HEAD DETAIL.PDF
- DB-SSD06-T604 INTEGRAL GARAGE DOOR THRESH.PDF

Window Details

- DB-SSD07-T601 WINDOW HEAD DETAIL.PDF
- DB-SSD07-T602 WINDOW CILL DETAIL.PDF
- DB-SSD07-T603 WINDOW DETAIL HORIZONTAL SECTION.PDF
- DB-SSD07-T604 FULL HEIGHT REAR BAY HEAD DETAIL.PDF
- DB-SSD07-T605 FULL HEIGHT REAR BAY JAMB DETAIL.PDF

Services

- DB-SSD09-T601 GAS PIPE THROUGH GROUND FLOOR WALL.PDF
- DB-SSD09-T602 GAS PIPE ENTRY AT GROUND FLOOR WALL.PDF
- DB-SSD09-T603 VERTICAL GAS PIPE ENCLOSURE IN EXTERNAL WALL
- DB-SSD09-T604 VERTICAL GAS PIPE RISER AT UPPER FLOORS.
- DB-SSD09-T606 BALANCED FLUE BOILER ON EXTERNAL WALL. DF
- DB-SSD09-T607 PARTY WALL SERVICES DETAIL.PDF
- DB-SSD09-T608 PARTY WALL SERVICES DET AL 1.PL
- DB-SSD09-T609 SEPERATING GARAGE WALL SERVICE DETAIL.PDF •
- DB-SSD09-T610 RECESSED GAS METER BOX DETAIL.PDF
- DB-SSD09-T611 RECESSED GAS METER BOX DETAIL 1.PDF
- DB-SSD09-T612 BT INSTALLATION SHEET 1.PDF
- DB-SSD09-T613 BT INSTALLATION SHEET C.PDF
- DB-SSD09-T614 JJI JOIST SERVICE NOTCHINGS.PDF

Sanitary

- DB-SSD10-T601 SANITAR ROBUST WALL CONSTRUCTION.PDF DB-SSD10-T602 SHOVER TRAY INSTALLATION DETAIL SHEET 1.PDF
- DB-SSD10-T603 + SHOWER TRAY INSTALLATION DETAIL SHEET 2.PDF

